

KAESER DENTAL

Advanced, quiet and powerful



**High
quality cylinder**



Control panel



Dental dryers



PPS control unit
(PERMANENT-POWER-SYSTEM)

- Made in Germany to KAESER's renowned quality standards
- A special energy-saving Seccomat DENTAL dryer is optionally available to ensure a reliable source of quality, dry dental compressed air
- Up to 90 % compressed air availability with KAESER's PERMANENT-POWER-SYSTEM (PPS)
- KAESER's decades of experience in compressed air engineering and technology guarantee outstanding performance and durability

Technical specifications

Model	Compressed air quality	Suitable for treatment units Number	Flow rate at 5 bar		Max. pressure bar	Air receiver volume l	Motor power kW	Sound pressure level ¹⁾ dB(A)	Dimensions W x D x H mm
			Peak l/min	Continuous operation l/min					
Dental 1 T	As per EN ISO 7494-2:2003, Dentistry – Dental Units Part 2: Water and Air Supply (ISO 7484-2:2003)	1	65	52	7	24	0.75	64 (51)*	490 x 420 x 740
Dental 3 T		2-3	158	135	7	24	2.2 (1.4)**	69 (59)*	500 x 500 x 730
Dental 5 T		5	262	225	7	65	2.2	69 (59)*	510 x 510 x 960
Dental 5/2 T		10-12	524	472	7	90	2 x 2.2	71	1200 x 540 x 840

*) With sound enclosure **) Installed motor power (compressor power requirement)

¹⁾ Sound pressure level as per ISO 2151 and the basic standard ISO 9614-2, tolerance: ± 3 dB (A)



KAESER KOMPRESSOREN SE

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel +49 9561 640-0 – Fax +49 9561 640130

e-mail: productinfo@kaeser.com – www.kaeser.com